



# **CERTIFICATE OF COMPLIANCE**

We hereby certify that our products (see list below) were manufactured in accordance with our current specifications of materials and production processes and have been inspected to comply with all quality assurance criteria. All temperature monitoring was performed with temperature logger ALMEMO, model 2590 (serial number H09100824), verified by A.COM calibration laboratory certified ISO/IEC Standard 17025:2005 and NIST traceable (see appendix A).

Product Code	Description	Batch Number	Expiry Date
TP278	Blood Temp 10 °C (BT10)	AR 1976-4	09/2025

Retiben Soncino
Chief Quality Officer Timestrip
Chief Quality Officer

**April 23, 2023 Date** 



**Quality Assurance Dept.** 

### Appendix A



Page 1 of 4

#### **Calibration Certificate**

Certificate Number:

3092908

Date of Issue: 27/04/2022

Name and signature of person carried out the test: Izik. Mishan Lab Man.

Approved signatory typed name:

Moshe. Appleboum CEO

Customer Name:

**TIMESTRIP** 

Customer Address:

Identification of item calibrated:

Description: THERMOMETER

Manufac.

**ALMEMO** 

Model:

25906

S/N: Inventory:

H09100824 TM-03

As Found Conditions:

Proper

Date of receipt of item:

27/04/2022

Date of performance of test:

27/04/2022

Environment details:

TEMPERATURE 23°C±3°C; HUMIDITY 30% - 70%

**Testing Description:** 

The calibration process was preformed according to Acom procedures and based on Acom traceability. The calibration values for the unit under test was performed by calculate the indicated value and applied value from the reference standards. The calibration preformed according to Acom procedures No. 08-10A to 08-70A

#### **Testing Recommendation**

Description of specific test or method used:

<u>Model</u>	Serial No.	V.O.C.	
TESTO 174H	3660256	01/07/2022	
OMEGAETTE HH311	171202193	01/07/2022	
FLUKE 2605	5129806	01/07/2022	
FLUKE 5500A	6715008	01/07/2022	
PMI-108	108-M-1001	01/07/2022	
PT100	6517	01/07/2022	

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%



Technical Services Ltd.

## Quality Assurance Dept.



Certificate Number: 3092908

Page 2 of 4

Test Summary:

est Summary:							
<u>Test</u>	<u>Test</u> <u>Str</u>			atus			
1) TEMP	WILL SEALS ASSESSED WAS INCOMED ON PRINTED			Pass			
The state of the s							
2) TEMPERATURE M1 (PT100-2)				Pass			
<ol><li>TEMPERATURE M2 (PT100-2)</li></ol>			Pa				
<ol> <li>TEMPE</li> </ol>	ERATURE MO (PT	Γ100-1)	Pa	ass			
5) TEMP	ERATURE M1 (P1	T100-1)	100-1) Pa		ass		
A CONTRACT TO A CONTRACT OF THE CONTRACT OF TH	ERATURE M2 (P1	1211		ass			
		1100-1)	F	455			
TEMPERATURE							
Test Point	<u>Applied</u>	Indicated V	'alue Difference	Tolerance	<u>Uncertainty</u>	<u>Status</u>	
-25ºC	-25 00	-25.15	-0.15	± 0.75	0.3	Pass	
0 <sub>6</sub> C	0.00	-0.17	-0,17	± 0,75	0.3	Pass	
25ºC	25.00	24.88	-0.12	± 0.75	0.3	Pass	
50°C	50.00	49.84	-0.16	± 0.75	0.3	Pass	
75ºC 100ºC	75.00 100.00	74.55 99.97	-0.45 -0.03	± 1 ± 1	0.4	Pass Pass	
		33.37	0.03	1 1	0.4	F 033	
<b>TEMPERATURE</b>	M1 (PT100-2)						
Test Point	Applied	Indicated V	alue Difference	Tolerance	Uncertainty	Status	
-25ºC	-25.00	-25.16	-0.16	± 0.75	0.3	Pass	
0ºC	0.00	-0.11	-0.11	± 0.75	0.3	Pass	
25°C	25.00	24.86	-0.14	± 0.75	0.3	Pass	
50ºC	50.00	49.99	-0.01	t 0.75	0.3	Pass	
75ºC	75,00	74.93	-0,07	± 1	0.4	Pass	
100ºC	100.00	99.91	-0.09	* 1	0.4	Pass	
TEAADED A TILIDE	MO (DT400 0)						
<b>TEMPERATURE</b>	MZ (P1100-Z)						
Test Point	<u>Applied</u>	Indicated V	<u>'alue Difference</u>	<u>Tolerance</u>	<u>Uncertainty</u>	<u>Status</u>	
-25ºC	-25.00	-25.12	-0.12	± 0.75	0.3	Pass	
OPC	0,00	-0.01	-0.01	± 0.75	0.3	Pass	
25ºC	25.00	24.98	-0.02	± 0.75	0.3	Pass	
50ºC	50,00	49.92	-0.08	± 0,75	0.3	Pass	
75ºC	75,00	74.81	-0.19	± 1	0.4	Pass	
100gC	100,00	99.84	-0.16	± 1	0.4	Pass	
EMPERATURE	M0 (PT100-1)						
Test Point	Applied	Indicated V	Indicated Value Difference		Uncertainty	Status	
-25ºC	-25,00	-25.26	-0.26	Tolerance ± 0.75	0,3	Pass	
0ºC	0.00	-0.13	-0.13	± 0.75	0.3	Pass	
25ºC	25,00	24.84	-0.16	± 0.75	0.3	Pass	
50°C	50.00	49.81	-0.19	± 0.75	0.3	Pass	
75ºC	75.00	74.83	-0-17	± 1	0.4	Pass	
100ºC	100.00	99.81	-0.19	* 1	0.4	Pass	
EMPERATURE	M1 (PT100-1)						
Test Point	Applied	Indicated V	alue Difference	Tolerance	Uncertainty	Status	
-25°C	-25.00	-25.1	-0.10	± 0.75	0.3	Pass	
0aC	0.00	-0.14	-0.14	± 0.75	0.3	Pass	
25ºC	25.00	24.86	-0.14	± 0.75	0.3	Pass	
50ºC	50.00	49.9	-0.10	± 0.75	0.3	Pass	
75ºC	75.00	74.87	-0.13	± 1	0.4	Pass	
100ºC	100.00	99.88	-0.12	± 1	0.4	Pass	
EMPERATURE	M2 (PT100-1)						
Test Point	Applied	Indicated V	alue Difference	<u>Tolerance</u>	Uncertainty	Status	
		-25.04	-0.04	± 0.75	0.3	Pass	
-25ºC	-25.00		,			Pass	
-25°C 0°C	-25.00 0.00	-0.15	-0.15	± 0.75	0.3		
-25ºC 0ºC 25ºC	0.00	-0.15 24.56	-0.15 -0.44	± 0.75 ± 0.75	0.3	Pass	
0aC		-0.15 24,56 49,85	-0.15 -0.44 -0.15	± 0.75 ± 0.75 ± 0.75	0.3		
0ºC 25ºC	0.00 25.00	24.56	-0.44	£ 0.75	0.3	Pass	

A.com certifies that the performance of the above instrument has been verified using test equipment and known accuracy which is traceable to the U.S. National Institute of Standards and Technology (NIST).

The policies are procedures at this facility are based on ANSI/ISO/IEC Standard 17025-2017. This cortificate shall not