

CERTIFICATE OF COMPLIANCE

We hereby certify that our products (see list below) were manufactured in accordance with our current specifications of materials and production processes and have been inspected to comply with all quality assurance criteria. All temperature monitoring was performed with temperature logger ALMEMO, model 2590 (serial number H09100824), verified by A.COM calibration laboratory certified ISO/IEC Standard 17025:2005 and NIST traceable (see appendix A).

| Description | Batch Number | Expiry Date |
|-------------------------|--------------|-------------|
| Blood Temp 10 °C (BT10) | AR 1923-3 | 11/2024 |
| | 1 | |

Reuben Soncino Chief Quality Officer Timestrip

Chief Quality Officer

June 6, 2022 Date



Technical Services Ltd.

Quality Assurance Dept.

Appendix A

Electronic Measurement Technology

Page 1 of 4

Calibration Certificate

Certificate Number:

3092908

Date of Issue: 27/04/2022

Name and signature of person carried out the test: Izik. Mishan Lab Man.

Approved signatory typed name:

Moshe. Appleboum CEO

Customer Name:

TIMESTRIP

Customer Address:

Identification of item calibrated:

Description: THERMOMETER

Manufac.

ALMEMO

Model:

25906

S/N:

H09100824

Inventory:

TM-03

As Found Conditions:

Proper

Date of receipt of item:

27/04/2022

Date of performance of test:

27/04/2022

Environment details:

TEMPERATURE 23°C±3°C; HUMIDITY 30% - 70%

Testing Description:

The calibration process was preformed according to Acom procedures and based on Acom traceability. The calibration values for the unit under test was performed by calculate the indicated value and applied value from the reference standards. The calibration preformed according to Acom procedures No. 08-10A to 08-70A

Testing Recommendation

Description of specific test or method used:

| <u>Model</u> | Serial No. | V.O.C. |
|-----------------|------------|------------|
| TESTO 174H | 3660256 | 01/07/2022 |
| OMEGAETTE HH311 | 171202193 | 01/07/2022 |
| FLUKE 2605 | 5129806 | 01/07/2022 |
| FLUKE 5500A | 6715008 | 01/07/2022 |
| PMI-108 | 108-M-1001 | 01/07/2022 |
| PT100 | 6517 | 01/07/2022 |

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%

Technical Services Ltd.

Quality Assurance Dept.



Page 2 of 4

| Pass | Certificate Number: | 3092908 | | | | | | |
|--|--|--|-------------|------------------|-----------------|--|---|--|
| 1 TEMPERATURE M0 (PT100-2) | est Summary: | | | | | | | |
| 1 TEMPERATURE M0 (PT100-2) | _ | | | | | | | |
| 2) TEMPERATURE M1 (PT100-2) Pass 4) TEMPERATURE M2 (PT100-1) Pass 5) TEMPERATURE M2 (PT100-1) Pass 6) TEMPERATURE M2 (PT100-1) Pass 6) TEMPERATURE M3 (PT100-1) Pass TEMPERATURE M3 (PT100-1) Pass TEMPERATURE M3 (PT100-1) Pass TEMPERATURE M3 (PT100-1) Pass TEMPERATURE M4 (PT100-2) Pass TEMPERATURE M5 (PT100-1) Pass TEMPERATURE M6 (PT100-2) Pass TEMPERATURE M6 (PT100-2) Pass TEMPERATURE M6 (PT100-2) Pass TEMPERATURE M6 (PT100-2) Pass TEMPERATURE M7 (PT100-2) Pass TEMPERATURE M8 (PT100-2) Pass TEMPERATURE M8 (PT100-2) Pass TEMPERATURE M9 (PT100-1) Pass TEMPERATURE M9 (| Test | <u>s</u> | | | <u>tatus</u> | | | |
| 3 TEMPERATURE M2 (PT100-1) Pass 4 TEMPERATURE M0 (PT100-1) Pass 5 TEMPERATURE M1 (PT100-1) Pass 6 TEMPERATURE M2 (PT100-1) Pass 6 TEMPERATURE M2 (PT100-1) Pass 7 TEMPERATURE M2 (PT100-1) Pass 7 TEMPERATURE M2 (PT100-2) Pass 7 TEMPERATURE M1 (PT100-2) Pass 7 TEMPERATURE M1 (PT100-2) Pass 7 TEMPERATURE M1 (PT100-2) Pass 7 TEMPERATURE M2 (PT100-2) Pass 7 TEMPERATURE M3 (PT100-1) | 1) TEMP | ERATURE M0 (P1 | Г100-2) | F | ass | | | |
| | 2) TEMP | TEMPERATURE M1 (PT100-2) | | F | ass | | | |
| S | 3) TEMP | 3) TEMPERATURE M2 (PT100-2) | | F | Pass | | | |
| | 4) TEMP | ERATURE M0 (P1 | Г100-1) | P | Pass | | | |
| TEMPERATURE M2 (PT100-1) | | 5) TEMPERATURE M1 (PT100-1) | | P | Pass | | | |
| Test Point | | | | | | | | |
| Post Point | O TEIVII | LIVITORE ME (I | 1100 1) | | 433 | | | |
| 22-90 | | E M0 (PT100-2) | | | | | | |
| Poec 0.00 | | . Personal de la companya de la comp | | | | *************************************** | Status | |
| \$ 2500 | | | | | | | | |
| September South | | | | | | | | |
| 1 | | | | | | 222 | | |
| Topic | | | | | | | | |
| Post Point | | | | | | | | |
| | EMPERATURE | M1 (PT100-2) | | | | | | |
| 259°C 25.00 -25.16 -0.16 ± 0.75 0.3 Pass 00°C 0.00 -0.11 -0.11 ± 0.75 0.3 Pass 590°C 50.00 49.99 -0.01 ± 0.75 0.3 Pass 590°C 75.00 74.93 -0.07 ± 1 0.4 Pass 100°C 100.00 99.91 -0.09 ± 1 0.4 Pass 100°C 100.00 99.91 -0.09 ± 1 0.4 Pass 100°C 100.00 99.91 -0.09 ± 1 0.4 Pass 250°C 25.00 -25.12 -0.12 ± 0.75 0.3 Pass 250°C 25.00 -25.12 -0.12 ± 0.75 0.3 Pass 250°C 25.00 -26.13 -0.01 ± 0.75 0.3 Pass 250°C 25.00 24.98 -0.01 ± 0.75 0.3 Pass 250°C 25.00 24.98 -0.06 ± 0.75 0.3 Pass 250°C 50.00 49.92 -0.08 ± 0.75 0.3 Pass 250°C 75.00 74.81 -0.19 ± 1 0.4 Pass 250°C 75.00 74.81 -0.19 ± 1 0.4 Pass 250°C 75.00 74.81 -0.19 ± 1 0.4 Pass 250°C 75.00 -25.26 -0.26 ± 0.75 0.3 Pass 250°C 25.00 -25.26 -0.26 ± 0.75 0.3 Pass 250°C 0.00 -0.13 -0.13 ± 0.75 0.3 Pass 250°C 25.00 -25.26 -0.26 ± 0.75 0.3 Pass 250°C 25.00 -25.26 -0.26 ± 0.75 0.3 Pass 250°C 25.00 -25.26 -0.26 ± 0.75 0.3 Pass 250°C 25.00 -24.84 -0.16 ± 0.75 0.3 Pass 250°C 25.00 -24.84 -0.16 ± 0.75 0.3 Pass 250°C 25.00 -24.84 -0.16 ± 0.75 0.3 Pass 250°C 25.00 -24.86 -0.14 ± 0.75 0.3 Pass 250°C 25.00 -24.86 -0.14 ± 0.75 0.3 Pass 250°C 25.00 -25.1 -0.10 ± 0.75 0.3 Pass 250°C 25.00 -24.86 -0.14 ± 0.75 0.3 Pass 250°C 25.00 -25.1 -0.10 ± 0.75 0.3 Pass 250°C 25.00 -25.04 -0.04 ± 0.75 0.3 Pass 250°C 25.00 -25.04 -0.04 ± 0.75 0.3 Pass 250°C 25.00 -25.04 -0.04 | | | Indicated \ | /alue Difference | Tolerance | Uncertainty | Status | |
| Part | 10.25-11 11 10 10 10 10 10 10 10 10 10 10 10 1 | | - | | | | 200000000000000000000000000000000000000 | |
| 50% 50,00 49,99 -0.01 1 0,75 0.3 Pass 75% 75,00 74,93 -0.07 1 1 0,40 Pass 100% 100,00 99,91 -0.09 1 1 0,40 Pass 75% | | | | | | | | |
| 75,90 | 25ºC | 25,00 | 24.86 | -0.14 | 1 0.75 | 0.3 | Pass | |
| Test Point Applied Indicated Value Difference Tolerance Uncertainty State Value Valu | 20°C | 50.00 | 49,99 | -0.01 | ± 0.75 | 0.3 | Pass | |
| Test Point | | | | | | | | |
| Test Point | 100°C | 100.00 | 99.91 | -0.09 | * 1 | 0.4 | Pass | |
| -259°C -25.00 -25.12 -0.12 ± 0.75 0.3 Poss -09°C 0.00 -0.01 -0.01 ± 0.75 0.3 Poss -09°C 50.00 24.98 -0.02 ± 0.75 0.3 Poss -09°C 50.00 49.92 -0.08 ± 0.75 0.3 Poss -09°C 50.00 74.81 -0.19 ± 1 0.4 Poss -09°C 100.00 99.84 -0.16 ± 1 0.4 Poss -09°C 100.00 99.84 -0.16 ± 1 0.4 Poss -09°C 100.00 -25.26 -0.26 ± 0.75 0.3 Poss -09°C 25.00 -25.26 -0.26 ± 0.75 0.3 Poss -09°C 25.00 24.84 -0.16 ± 0.75 0.3 Poss -09°C 25.00 24.84 -0.16 ± 0.75 0.3 Poss -09°C 50.00 49.81 -0.19 ± 1 0.4 Poss -09°C 50.00 39.81 -0.19 ± 1 0.4 Poss -09°C 50.00 39.81 -0.19 ± 1 0.4 Poss -09°C 100.00 39.81 -0.19 ± 1 0.4 Poss -09°C 100.00 39.81 -0.19 ± 1 0.4 Poss -09°C 25.00 -25.1 0.10 ± 0.75 0.3 Poss -09°C 25.00 -25.1 0.10 ± 0.75 0.3 Poss -09°C 25.00 -25.1 0.10 ± 0.75 0.3 Poss -09°C 25.00 24.86 -0.14 ± 0.75 0.3 Poss -09°C 25.00 24.86 -0.14 ± 0.75 0.3 Poss -09°C 25.00 24.86 -0.14 ± 0.75 0.3 Poss -09°C 50.00 49.9 -0.10 ± 0.75 0.3 Poss -09°C 50.00 49.87 -0.13 ± 1 0.4 Poss -09°C 50.00 49.87 -0.13 ± 1 0.4 Poss -09°C 50.00 24.86 -0.14 ± 0.75 0.3 Poss -09°C 50.00 49.9 -0.10 ± 0.75 0.3 Poss -09°C 50.00 24.87 -0.13 ± 1 0.4 Poss -09°C 50.00 24.87 -0.13 ± 1 0.4 Poss -09°C 50.00 24.87 -0.13 ± 1 0.4 Poss -09°C 50.00 50.50 50.50 50.50 50.50 50.50 50.50 | EMPERATURE | M2 (PT100-2) | | | | | | |
| 09°C 0,00 -0,01 -0,01 ± 0,75 0,3 Pass 25°C 25,00 24,98 -0,02 ± 0,75 0,3 Pass 509°C 50,00 49,92 -0,08 ± 0,75 0,3 Pass 75°C 75,00 74,81 -0,19 ± 1 0,4 Pass 100°C 100,00 99,84 -0,16 ± 1 0,4 Pass EMPERATURE MO (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25°C 25,00 -25,26 -0,26 ± 0,75 0,3 Pass 50°C 50,00 49,81 -0,19 ± 0,75 0,3 Pass 100°C 50,00 49,81 -0,19 ± 0,75 0,3 Pass 100°C 50,00 49,81 -0,19 ± 0,75 0,3 Pass 100°C 50,00 99,81 -0,19 ± 1 0,4 Pass EMPERATURE MI (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu 25°C 75,00 74,83 -0,17 ± 1 0,4 Pass EMPERATURE MI (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu 25°C 25,00 -25,1 0,10 ± 0,75 0,3 Pass 90°C 25,00 -25,1 0,10 ± 0,75 0,3 Pass 90°C 25,00 24,86 0,14 ± 0,75 0,3 Pass 50°C 25,00 24,86 0,14 ± 0,75 0,3 Pass 50°C 25,00 24,86 0,14 ± 0,75 0,3 Pass 50°C 75,00 74,87 -0,13 ± 1 0,4 Pass EMPERATURE M2 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25°C 25,00 24,86 0,14 ± 0,75 0,3 Pass 50°C 75,00 74,87 -0,13 ± 1 0,4 Pass EMPERATURE M2 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25°C -25,00 -25,04 -0,04 ± 0,75 0,3 Pass 90°C 0,00 -0,15 -0,15 +0,75 0,3 Pass 90°C 0,00 -0,15 -0,15 +0,75 0,3 Pass 90°C -25,00 -25,04 -0,04 ± 0,75 0,3 Pass 90° | Test Point | Applied | Indicated \ | /alue Difference | Tolerance | Uncertainty | Status | |
| 25.9°C 25.00 24.98 -0.02 -0.75 0.3 Pass 50°C 50.00 49.92 -0.08 +0.75 0.3 Pass 75°C 75.00 74.81 -0.19 +1 0.4 Pass 100°C 100.00 99.84 -0.16 +1 0.4 Pass | | | | | | 0.3 | Pass | |
| Son | | | | | | | | |
| 75,9°C | | | | | | | | |
| Test Point Applied Indicated Value Difference Tolerance Uncertainty Statute Pass | | | | | | | | |
| Test Point Applied Indicated Value Difference Tolerance Uncertainty Statute Stat | | | | | | | | |
| Test Point | | | | | | | | |
| -25%C -25.00 -25.26 -0.26 ± 0.75 0.3 Pass 0%C 0.00 -0.13 -0.13 ± 0.75 0.3 Pass 25%C 25.00 24.84 -0.16 ± 0.75 0.3 Pass 50%C 50.00 49.81 -0.19 ± 0.75 0.3 Pass 100%C 75.00 74.83 -0.17 ± 1 0.4 Pass 100%C 100.00 99.81 -0.19 ± 1 0.4 Pass 100%C 100.00 99.81 -0.19 ± 1 0.4 Pass 100%C 100.00 99.81 -0.19 ± 1 0.4 Pass EMPERATURE M1 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25%C -25.00 -25.1 -0.10 ± 0.75 0.3 Pass 0%C 0.00 -0.14 -0.14 ± 0.75 0.3 Pass 50%C 25.00 24.86 -0.14 ± 0.75 0.3 Pass 50%C 50.00 49.9 -0.10 ± 0.75 0.3 Pass 50%C 75.00 74.87 -0.13 ± 1 0.4 Pass 100%C 100.00 99.88 -0.12 ± 1 0.4 Pass EMPERATURE M2 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25%C 75.00 74.87 -0.13 ± 1 0.4 Pass EMPERATURE M2 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25%C -25.00 -25.04 -0.14 ± 0.75 0.3 Pass 0%C 0.00 49.98 -0.15 ± 0.75 0.3 Pass 0%C 0.000 -0.15 -0.15 ± 0.75 0.3 Pass 25%C -25.00 -25.04 -0.04 ± 0.75 0.3 Pass 0%C 0.000 -0.15 -0.15 ± 0.75 0.3 Pass 0%C 0.000 -0.15 -0.15 ± 0.75 0.3 Pass 0%C 0.000 -0.15 -0.15 ± 0.75 0.3 Pass 0%C 0.000 49.85 -0.15 ± 0.75 0.3 Pass 0%C 0.000 49.85 -0.15 ± 0.75 0.3 Pass 0%C 0.000 49.85 -0.15 ± 0.75 0.3 Pass | CALL TO THE REAL PROPERTY OF THE PARTY OF TH | | 1 (2 4 4) | / I Bize | -0.4 5050000000 | Participation of the second second | - | |
| 0°C 0.00 -0.13 -0.13 ± 0.75 0.3 Pass 25°C 25.00 24.84 -0.16 ± 0.75 0.3 Pass 50°C 50.00 49.81 -0.19 ± 0.75 0.3 Pass 75°C 75.00 74.83 -0.17 ± 1 0.4 Pass 100°C 100.00 99.81 -0.19 ± 1 0.4 Pass EMPERATURE M1 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25°C 25.00 -25.1 -0.10 ± 0.75 0.3 Pass 50°C 25.00 -24.86 -0.14 ± 0.75 0.3 Pass 50°C 50.00 49.9 -0.10 ± 0.75 0.3 Pass 100°C 100.00 99.88 -0.12 ± 0.75 0.3 Pass 100°C 75.00 74.87 -0.13 ± 1 0.4 Pass <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> | | | | | | | | |
| 25°C 25.00 24.84 -0.16 ± 0.75 0.3 Pass | | | | | | | | |
| Some | | | | | | | | |
| 75.00 | | | | | | | | |
| Test Point | | | | | | | | |
| Test Point | 100°C | 100.00 | 99.81 | -0.19 | ± 1 | 0.4 | Pass | |
| Test Point | EMPERATURE | M1 (PT100-1) | | | | | | |
| -25°C 25.00 -25.1 -0.10 ± 0.75 0.3 Pass 0°C 0.00 -0.14 -0.14 ± 0.75 0.3 Pass 25°C 25.00 24.86 -0.14 ± 0.75 0.3 Pass 100°C 50.00 49.9 0.10 ± 0.75 0.3 Pass 100°C 75.00 74.87 -0.13 ± 1 0.4 Pass 100°C 100.00 99.88 0.12 ± 1 0.4 Pass 100°C 100.00 99.88 0.12 ± 1 0.4 Pass 100°C PTIOO-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Status -25°C -25.00 -25.04 -0.04 ± 0.75 0.3 Pass 25°C 25.00 24.56 0.44 ± 0.75 0.3 Pass 25°C 25.00 24.56 0.44 ± 0.75 0.3 Pass 25°C 25.00 49.85 0.15 ± 0.75 0.3 Pass 25°C 25.00 24.56 0.44 ± 0.75 0.3 Pass 25°C 25.00 25°C 25.00 24.56 0.44 ± 0.75 0.3 Pass 25°C 25°C 25°C 25°C 25°C 25°C 25°C 25°C | 2 2 50 | 20 0 0 | Indicated V | /alue Difference | Tolerance | Uncertainty | Status | |
| 0°C 0.00 -0.14 -0.14 ± 0.75 0.3 Pass 25°C 25.00 24.86 -0.14 ± 0.75 0.3 Pass 50°C 50.00 49.9 -0.10 ± 0.75 0.3 Pass 75°C 75.00 74.87 -0.13 ± 1 0.4 Pass EMPERATURE M2 (PT100-1) Temperature M2 (PT100-1) Tolerance Uncertainty Statu -25°C -25.00 -25.04 -0.04 ± 0.75 0.3 Pass 0°C 0.00 -0.15 -0.15 ± 0.75 0.3 Pass 50°C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50°C 30.00 49.85 -0.15 ± 0.75 0.3 Pass 50°C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50°C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | ALL SHOWS AND A SECURITY OF | | | | | Committee and Continue to Cont | | |
| 25°C 25.00 24.86 -0.14 ± 0.75 0.3 Pass | | | | | | | | |
| \$50.00 | | | | | | | | |
| 100 °C 100.00 99.88 -0.12 ± 1 0.4 Pass EMPERATURE M2 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25 °C -25.00 -25.04 -0.04 ± 0.75 0.3 Pass 0 °C 0.00 -0.15 -0.15 ± 0.75 0.3 Pass 25 °C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50 °C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | 50°C | 50.00 | 49.9 | | | 0.3 | | |
| EMPERATURE M2 (PT100-1) Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu ~25°C ~25.00 ~25.04 ~0.04 ± 0.75 0.3 Pass 0°C 0.00 -0.15 + 0.15 ± 0.75 0.3 Pass 25°C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50°C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | | | | | | 0.4 | Pass | |
| Test Point Applied Indicated Value Difference Tolerance Uncertainty Statu -25%C -25.00 -25.04 -0.04 ± 0.75 0.3 Pass 0°C 0.00 -0.15 -0.15 ± 0.75 0.3 Pass 25°C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50°C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | 100aC | 100.00 | 99.88 | -0.12 | ± 1 | 0.4 | Pass | |
| -25°C -25.00 -25.04 -0.04 ± 0.75 0.3 Pass 0°C 0.00 -0.15 -0.15 ± 0.75 0.3 Pass 25°C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50°C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | EMPERATURE | M2 (PT100-1) | | | | | | |
| O°C 0.00 -0.15 -0.15 + 0.75 0.3 Pass 25°C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50°C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | Test Point | Applied | Indicated V | alue Difference | Tolerance | Uncertainty | Status | |
| 25°C 25.00 24.56 -0.44 ± 0.75 0.3 Pass 50°C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | -25°C | -25.00 | -25 04 | -0.04 | | | Pass | |
| 50°C 50.00 49.85 -0.15 ± 0.75 0.3 Pass | | 0.00 | -0.15 | -0.15 | | 0.3 | | |
| | | | | | | | Pass | |
| 75°C 75.00 74.86 -0.14 1 1 0.4 Pass | | | | | | | | |
| 100°C 100.00 99.9 -0.10 ± 1 0.4 Pass | | | | | | | | |

A.com certifies that the performance of the above instrument has been verified using test equipment and known accuracy which is traceable to the U.S. National Institute of Standards and Technology (NIST).

The policies are procedures at this facility are based on ANSI/ISO/IEC Standard 17025:2017. This certificate shall not reproduced, except in full without the written approval of the calibration facility