

Quality Assurance Dept.

CERTIFICATE OF COMPLIANCE

We hereby certify that our products (see list below) were manufactured in accordance with our current specifications of materials and production processes and have been inspected to comply with all quality assurance criteria. All temperature monitoring was performed with temperature logger ALMEMO, model 2590 (serial number H09100824), verified by A.COM calibration laboratory certified ISO/IEC Standard 17025:2005 and NIST traceable (see appendix A).

Product Code	Description	Batch Number	Expiry Date
TP278	Blood Temp 10 °C (BT10)	AR 1958-4	03/2025

Remben Soncino
Chief Quality Officer Timestrip

Chief Quality Officer

January 4, 2023 Date



Quality Assurance Dept.

Appendix A



Page 1 of 4

Calibration Certificate

Certificate Number:

3092908

Date of Issue: 27/04/2022

Name and signature of person carried out the test: Izik. Mishan Lab Man.

Approved signatory typed name:

Moshe, Applebourn CEO

Customer Name:

TIMESTRIP

Customer Address:

Identification of item calibrated:

Description: THERMOMETER

Manufac.

ALMEMO

Model:

25906

S/N: Inventory: H09100824 TM-03

As Found Conditions:

Proper

Date of receipt of item:

27/04/2022

Date of performance of test:

27/04/2022

Environment details:

TEMPERATURE 23°C±3°C; HUMIDITY 30% - 70%

Testing Description:

The calibration process was preformed according to Acom procedures and based on Acom traceability. The calibration values for the unit under test was performed by calculate the indicated value and applied value from the reference standards. The calibration preformed according to Acom procedures No. 08-10A to 08-70A

Testing Recommendation

Description of specific test or method used:

Model	Serial No.	VOC.
TESTO 174H	3660256	01/07/2022
OMEGAETTE HH311	171202193	01/07/2022
FLUKE 2605	5129806	01/07/2022
FLUKE 5500A	6715008	01/07/2022
PMI-108	108-M-1001	01/07/2022
PT100	6517	01/07/2022

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%



Technical Services Ltd.

Quality Assurance Dept.



Certificate Number: 3092908 Page 2 of 4

Test Summary:

est Summary:						
<u>Test</u>		<u>Status</u>				
1) TEMPERATURE M0 (PT100-2)			Pass			
	ERATURE M1 (PT					
		Pass				
				Pass		
4) TEMPE	ERATURE M0 (PT	100-1)	Pass			
5) TEMPERATURE M1 (PT100-1)			-1) Pass			
· ·	RATURE M2 (PT					
	NEW DESIGNATION OF THE PARTY OF	100 1)		400		
TEMPERATURE		1. 10. 11. 12				a
Test Point	<u>Applied</u>		/alue Difference	Tolerance	Uncertainty	<u>Status</u>
-25°C 0°C	-25.00 0.00	-25 15 -0 17	-0.15 -0.17	± 0.75	0.3	Pass
25ºC	25.00	24.88	-0.17	± 0.75	0.3	Pass Pass
50°C	50.00	49.84	-0.16	± 0.75	0.3	Pass
75ºC	75.00	74.55	-0,45	± 1	0.4	Pass
100°C	100.00	99.97	-0.03	± 1	0.4	Pass
TEMPERATURE	M1 (PT100-2)					
Test Point		Indicated \	/alue Difference	Tolerance	Uncertaint	Status
	<u>Applied</u> -25.00		/alue Difference	<u>Tolerance</u>	Uncertainty	Status
-25°C 0°C	-25.00	-25.16 -0.11	-0.16 -0.11	± 0.75 ± 0.75	0.3	Pass
25ºC	25.00	24.86	-0.14	± 0.75	0.3	Pass
50°C	50.00	49.99	-0.01	± 0.75	0.3	Pass
75ºC	75.00	74.93	-0.07	± 1	0.4	Pass
100°C	100.00	99.91	-0.09	± 1	0.4	Pass
TEMPERATURE	M2 (DT100 2)					
				- 4		.
<u>Test Point</u>	<u>Applied</u>		/alue Difference	<u>Tolerance</u>	<u>Uncertainty</u>	<u>Status</u>
-25ºC	-25.00	-25.12	-0.12	± 0.75	0.3	Pass
0 ₈ C	0.00	-0.01	-0.01	± 0.75	0.3	Pass
25ºC	25.00	24,98	-0.02	± 0.75	0.3	Pass
50°C	50.00	49.92 74.81	-0.08 -0.19	± 0.75 ± 1	0.3	Pass Pass
7500	75.00					
75°C 100°C	75.00 100.00		-0.16	± 1	0.4	Pass
100ºC	100.00	99.84	-0.16	* 1	0.4	Pass
100°C TEMPERATURE	100.00	99.84		* 1	0.4	Pass
100ºc TEMPERATURE Test Point	100.00 M0 (PT100-1) Applied	99.84 Indicated \	/alue Difference	Tolerance	0.4 Uncertainty	Pass Status
100%C TEMPERATURE Test Point -25%C	100.00 M0 (PT100-1) Applied -25.00	99.84 Indicated \ -25.26	/alue <u>Difference</u> -0.26	Tolerance	Uncertainty 0.3	Status Pass
100°C TEMPERATURE Test Point -25°C 0°C	100.00 M0 (PT100-1) Applied -25.00 0.00	99.84 Indicated \ -25,26 -0.13	/alue <u>Difference</u> -0.26 -0.13	<u>Tolerance</u> ± 0.75 ± 0.75	Uncertainty 0.3 0,3	<u>Status</u> Pass Pass
100°C TEMPERATURE Test Point -25°C 0°C 25°C	100.00 MO (PT100-1) <u>Applied</u> -25.00 0.00 25.00	99.84 Indicated \ -25.26 -0.13 24.84	Value Difference -0.26 -0.13 -0.16	Tolerance ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3	Status Pass Pass Pass
TEMPERATURE Test Point -25°C 0°C 25°C 50°C	100.00 MO (PT100-1) <u>Applied</u> -25.00 0.00 25.00 50.00	99.84 Indicated \(\sigma\) -25.26 -0.13 24.84 49.81	Value Difference -0.26 -0.13 -0.16 -0.19	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.3 0.3	Status Pass Pass Pass Pass
100°C TEMPERATURE Test Point -25°C 0°C 25°C	100.00 MO (PT100-1) <u>Applied</u> -25.00 0.00 25.00	99.84 Indicated \ -25.26 -0.13 24.84	Value Difference -0.26 -0.13 -0.16	Tolerance ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3	Status Pass Pass Pass
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00	99.84 Indicated V -25.26 -0.13 24.84 49.81 74.83	/alue Difference -0.26 -0.13 -0.16 -0.19 -0.17	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1	Uncertainty 0.3 0.3 0.3 0.3 0.3 0.4	Status Pass Pass Pass Pass Pass
TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE	100.00 MO (PT100-1) <u>Applied</u> -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1)	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1	Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4	Status Pass Pass Pass Pass Pass Pass Pass Pa
TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\)	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance	Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4	Status Pass Pass Pass Pass Pass Pass
TEMPERATURE Test Point -259C 09C 259C 509C 759C 1009C TEMPERATURE Test Point -259C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00	99.84 Indicated V -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated V -25.1	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75	Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4 Uncertainty 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00	99.84 Indicated V -25.26 -0.13 -24.84 49.81 74.83 99.81 Indicated V -25.1 -0.14	/alue Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 /alue Difference -0.10 -0.14	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 0°C 25°C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\) -25.1 -0.14 24.86	/alue Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 /alue Difference -0.10 -0.14	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00 50.00	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\) -25.1 -0.14 24.86 49.9	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.14 -0.10	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\) -25.1 -0.14 24.86 49.9 74.87	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.10 -0.13	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1	Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.4	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\) -25.1 -0.14 24.86 49.9	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.14 -0.10	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 75°C 100°C TEMPERATURE	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) M1 (PT100-1) M2 (PT100-1)	99.84 Indicated V -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated V -25.1 -0.14 24.86 49.9 74.87 99.88	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.10 -0.13 -0.12	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1	Uncertainty 0.3 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4 0.4	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point	100.00 M0 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 M1 (PT100-1) Applied Applied Applied Applied Applied	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\) -25.1 -0.14 24.86 49.9 74.87 99.88 Indicated \(\)	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.14 -0.10 -0.13 -0.12 Value Difference	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance	Uncertainty 0.3 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.4 0.4 Uncertainty	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 75°C 100°C TEMPERATURE Test Point -25°C 75°C 75°C 75°C 75°C 75°C 75°C TEMPERATURE Test Point -25°C	100.00 M0 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M2 (PT100-1) Applied -25.00	99.84 Indicated V -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated V -25.1 -0.14 24.86 49.9 74.87 99.88 Indicated V -25.04	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.14 -0.10 -0.13 -0.12 Value Difference -0.04	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.4 0.4	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C Test Point	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M2 (PT100-1) Applied -25.00 0.00 M2 (PT100-1) Applied -25.00 0.00	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\) -25.1 -0.14 24.86 49.9 74.87 99.88 Indicated \(\) -25.04 -0.15	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.14 -0.10 -0.13 -0.12 Value Difference -0.04 -0.15	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.4 0.4 Uncertainty 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 25°C 25°C 25°C 25°C 25°C 25°C 25	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 50.00 75.00 100.00 M2 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00	99.84 Indicated V -25.26 -0.13 74.84 49.81 74.83 99.81 Indicated V -25.1 -0.14 24.86 49.9 74.87 99.88 Indicated V -25.04 -0.15 24.56	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.14 -0.10 -0.13 -0.12 Value Difference -0.04 -0.15 -0.44	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.4 0.4 Uncertainty 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa
100°C TEMPERATURE Test Point -25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C 25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 50°C 75°C 100°C TEMPERATURE Test Point -25°C 0°C	100.00 MO (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M1 (PT100-1) Applied -25.00 0.00 25.00 50.00 75.00 100.00 M2 (PT100-1) Applied -25.00 0.00 M2 (PT100-1) Applied -25.00 0.00	99.84 Indicated \(\) -25.26 -0.13 24.84 49.81 74.83 99.81 Indicated \(\) -25.1 -0.14 24.86 49.9 74.87 99.88 Indicated \(\) -25.04 -0.15	Value Difference -0.26 -0.13 -0.16 -0.19 -0.17 -0.19 Value Difference -0.10 -0.14 -0.14 -0.10 -0.13 -0.12 Value Difference -0.04 -0.15	Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 1 ± 1 Tolerance ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75 ± 0.75	Uncertainty 0.3 0.3 0.3 0.4 0.4 Uncertainty 0.3 0.3 0.4 0.4 0.4 Uncertainty 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3	Status Pass Pass Pass Pass Pass Pass Pass Pa

A.com certifies that the performance of the above instrument has been verified using test equipment and known accuracy which is traceable to the U.S. National Institute of Standards and Technology (NIST).

The policies are precedures at this facility are based on ANSI/ISO/IEC Standard 1707E-2017. This cortificate shall not