



TC-25 TEMPCHECK Rapid Response Thermometer



PRODUCT DESCRIPTION:

The TC-25 TEMPCHECK Rapid Response Thermometer is a unique digital temperature verification system for blood, red blood cells (RBC), platelets, fresh frozen plasma (stored and thawed), cryoprecipitates (cryo), and other bagged biologics. Designed for hospital or laboratory use, the noninvasive CAP-TRM42470-compliant TC-25 TEMPCHECK thermometer eliminates the need for inaccurate, slow-responding “stick-on” temperature indicators.

When bagged blood products are used for transfusion, delivered to blood banks, or removed from, or returned to, cold storage refrigerators, temperature must be verified. The bag is placed directly onto the TC-25 TEMPCHECK’s flatbed base incorporating a specially designed rapid response embedded temperature sensor. In 15-30 seconds, the bulk temperature of the bag is displayed on the easy-to-read, angled display screen.

For lightweight portability or operation during a power outage, the TC-25 TEMPCHECK Rapid Response Thermometer includes a 3.6V LiPo rechargeable battery offering more than 7½ hours of temperature display running time. When operating on battery, the TC-25 TEMPCHECK will shut down to conserve battery life after 4 minutes of inactivity. Simply press and hold the POWER/EXIT button to reactivate the temperature display. The battery automatically recharges when the TC-25 TEMPCHECK is connected to line power.

FEATURES:

- (cryo), and other bagged biologics
- Rapid response time: 15 to 30 seconds
- Tightly targeted temperature range (0.0 – 40.0 °C) providing ± 0.2 °C accuracy
- Angled, easy-to-read back-lit display with 0.1 ° resolution
- User selectable temperature scale: °C or °F
- >7.5 hours LiPo rechargeable battery backup for easy portability
- Ships with a NIST-traceable “Certificate of Calibration”
- CAP TRM42470 compliant
- EU Declaration of Conformity

APPLICATIONS:

- Manual+: LED indicators if temperature is out of range
- Go/No Go: audio and visual alarms if temperature is out of range
- Continuously Monitor temperature of one bag while others are being batch processed
- Temperature verification of packaged blood bags containing blood, RBC, platelets, FFP, and cryo
- Temperature verification of blood bags upon delivery to blood banks
- Temperature verification of plasma and platelet bags in operating rooms and blood banks



For audio and visual temperature alarms when labeling or packaging batches of bags, see the TC-25+ TEMPCHECK.



TC-25 TEMPHECK Rapid Response Thermometer

Specifications:

Temperature Sensor & Display		
Sensor	Type K rapid-response thermocouple on an insulated pad	
Temperature Response Time	15 – 30 seconds	
Display Resolution	0.1 °C or °F	
Temperature Scale	°C	°F
Temperature Range	0.0 °C to 40.0 °C	32.0 °F to 104.0 °F
Accuracy	±0.2 °C	±0.4 °F
Temperature Display	Line Power	Temperature <u>display active</u> when TC-25 has line power.
	Battery Power	Press and hold POWER/EXIT button to activate temperature display for four minutes.

Power	Load	Supply
Power Requirements	12 VDC, 1 A, 12 W	100-240 VAC (fluctuation <150 mV peak-to-peak), 50/60 Hz, <0.35 <u>A RMS @</u> 115 VAC, UL listed

Battery Backup	
Rechargeable	1-cell, 3.6 V LiPo, battery charge regulator (BCR), >7.5 hours active use

Mechanical	
Mounting	Sits on benchtop, 4 ea. stiff rubber insulating feet
Dimensions, WxHxD	15.2 x 5.2 x 23.1 cm (6.0 x 2.1 x 9.1 in.)
Weight	466 g (1.0 lb.)
Case	ABS plastic

Environmental Conditions	
Facilities	Intended for indoor (laboratory) use
Altitude	Up to 2,000 meters (6,600')
Ambient Temperature Range	15 °C to 32 °C (59 °F to 90 °F)
Maximum Relative Humidity	60% (15 °C to 32 °C)
Ventilation	Compliance with ANSI/ASSP Z9.5-2022 recommended.
Pollution Degree	POLLUTION DEGREE 2: only non-conductive pollution occurs.

One-year warranty on all Hampshire Controls products.

